

Section 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Identifier

Product Name: BLACKWATTLE POTTERY UNDERGLAZE COLOURS

Product Code: **BUG** 01 Witchetty White, 02 Dragonfly Yellow, 04 Grasshopper Green , 05 Thrip Green, 06 Cricket Green, 09 Cuttle Bug Purple, 10 Stinkbug Pink, 11 Butterfly Blue, 12 Beetle Blue, 13 Scarab Blue, 14 Nymph Flesh, 15 Moth Brown, 17 Slater Grey, 18 Earwig Black

Other means of identification: Not Available

Relevant uses of the material:

Relevant identified uses: Ceramic, Glass and Pottery Based on available information, (provided the product is handled in accordance with this Safety Data Sheet, and used as supplied i.e. moist) is not classified as hazardous according to criteria of NOHSC.

Details of the Supplier of the SDS:

Registered Company Name: Blackwattle Pottery Pty. Ltd.

Address: 8 Aero Rd. INGLEBURN NSW 2565 Australia Telephone: 02 9829 5555

Email: <u>blackwattlepottery@bigpond.com</u> Website: <u>www.store.blackwattle.net.au</u>

Emergency telephone number

Emergency telephone number: 02 9829 5555 Business Hours Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 2 - HAZARDS IDENTIFICATION

Hazard Classification Classified as non-hazardous according to the criteria of NOHSC

Poisons Schedule: Not Applicable

Risk Phrases Not hazardous, no criteria found

Safety Phrases S22 Do not breath dust

Precautionary Statement(s) Prevention: Not Applicable

Precautionary Statement(s) Response: Not Applicable

Precautionary Statement(s) Storage: Not Applicable

Precautionary Statement(s) Disposal: Not Applicable



Date of Issue: 06/02/2022

| MATERIAL | PERCENTAGE | ACGIH TLV | |
|---------------------|------------|------------------------------|--|
| Zirconium Silicate | 0 - 9% | 5mg / m ³ (as Zr) | |
| Clay/ Potash | < 15% | Not Applicable | |
| Calcined Alumina | 0 - 2% | 10mg / m ³ | |
| Silica | 0 - 6% | 0.1mg / m ³ | |
| Zinc Oxide | 0 - 10% | 2mg / m ³ | |
| Lithium Carbonate | 0 - 10% | Not Applicable | |
| Magnesium Carbonate | 0 - 6% | Not Applicable | |

Section 3 - COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS number | Proportion |
|---------------------|------------|------------|
| Clay | 1332-58-7 | < 15% |
| Silica | 14808-60-7 | 0-6% |
| Zirconium Silicate | 10101-52-7 | 0 - 9% |
| Potash | 1302-78-9 | < 15% |
| Calcined Alumina | 1344-28-1 | 0 - 2% |
| Zinc Oxide | 1314-13-2 | 0 - 10% |
| Lithium Carbonate | 554-13-2 | 0 - 10% |
| Magnesium Carbonate | 7760-50-1 | 0 - 6% |

Section 4 - FIRST AID MEASURES:

| Eye Contact | If this product comes in contact with the eyes: rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if irritation persists. |
|---------------------|--|
| Ingestion | Rinse mouth. Do not induce vomiting. Seek medical advice. |
| | There is a danger of cumulative effects through ingestion and/or inhalation of silica dusts with prolonged or repeated exposures that may lead to delayed lung injury. |
| Inhalation | Move to fresh air. If breathing has stopped, apply artificial respiration and seek medical attention. |
| Skin contact | Wash off with soap and water. |
| General Information | You should call The Poisons Information Centre if you feel that you may have been poisoned |

General Information: You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126. Have this SDS with you when you call.

Advice to any immediate medical attention and special treatment needed: Treat symptomatically



Section 5 - FIRE FIGHTING MEASURES

| Suitable Extinguishing | Use appropriate fire extinguishing media for surrounding combustion materials involved in the fire |
|------------------------|---|
| Media Specific Methods | Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapors, fumes, dust or products of combustion |
| Specific Hazards | The product is noncombustible |
| HAZCHEM | Not Applicable |

Section 6 - ACCIDENTAL RELEASE MEASURES:

Clean up/DisposalFor small spills, pick up as much as possible, wipe area clean with damp sponge. For large spills,
pick up as much as possible, dispose of in closed containers, wash area with plenty of water.
Floors and work areas should be mopped with water.

Do not sweep work areas with a broom. Avoid the creation of airborne dust.

Environment No special environmental precautions required.

Personal Protection Wear apron or overalls, rubber gloves, chemical gloves or safety glasses.

Section 7 - HANDLING AND STORAGE:

Precaution for Safe Handling

Wear personal protective equipment.

Do not allow clothing wet with material to stay in contact with skin as this is likely to irritate skin.

Wash thoroughly after handling.

Keep containers sealed when not in use.

Condition for Safe Storage:

Store away from consumables.

Store in a cool place, away from heat and sunlight.

Storage incompatibility: None Known

Section 8 - EXPOSURE STANDARDS/ PERSONAL PROTECTION

National Exposure Standards Name



| STEL STEL (mgm3) (ppm) Silica 0.1 Biological Limit Values No I Other Exposure Information | TWA (mgm3) limit is allocated No exposure s Health & Safe respirable crys exposure limit | TWA (ppm) standard is established for this material by the National Occupational ty Commission (NOHSC), Australia, however the exposure standard for stalline silica, in the form of quartz, as set by NOHSC is given above. The t for dust otherwise not specified is TWA 0.1 mg/m3 (inspirable fraction) |
|---|--|---|
| (mgm3) (ppm) Silica 0.1 Biological Limit Values No I Other Exposure Information | (mgm3) limit is allocated No exposure s Health & Safe respirable crys exposure limit | (ppm) standard is established for this material by the National Occupational ty Commission (NOHSC), Australia, however the exposure standard for stalline silica, in the form of quartz, as set by NOHSC is given above. The |
| Silica 0.1 Biological Limit Values No I Other Exposure Information | limit is allocated No exposure s Health & Safe respirable crys exposure limit | standard is established for this material by the National Occupational ty Commission (NOHSC), Australia, however the exposure standard for stalline silica, in the form of quartz, as set by NOHSC is given above. The |
| Biological Limit Values No l Other Exposure Information | No exposure s Health & Safe respirable crys exposure limit | ty Commission (NOHSC), Australia, however the exposure standard for stalline silica, in the form of quartz, as set by NOHSC is given above. The |
| | Health & Safe respirable cry exposure limit | ty Commission (NOHSC), Australia, however the exposure standard for stalline silica, in the form of quartz, as set by NOHSC is given above. The |
| Fraincering Centrals | Coodycontilet | |
| Engineering Controls | required. The breathing zon maintain conc | ion adequate to maintain the concentration below exposure standards is use of a local exhaust ventilation system (drawing dust away from worker e) is recommended. If the engineering controls are not sufficient to centrations of particulates below the exposure standards, suitable rotection must be worn. |
| Exposure Controls/ Persona | al Protective Equip | oment |
| Eye/Face Protection | | eye/face protection should be worn if generating dust. Final choice of ye/face protection will vary according to individual circumstances. |
| Skin Protection | Wear imperview working with | ous protective gloves and protective clothing if skin contact is likely whilst this material. |
| Respiratory Protection | approved resp should be mad of Respiratory | controls are not effective in controlling airborne exposure then an birator with replaceable particulate filters should be used. Reference de to Australian Standards AS/NZS 1715, Selection, Use and Maintenance Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in e any necessary changes for individual circumstances. |



WARNING If clay dries to powder use PPE and avoid breathing dust.

| Appearance | Liquid | Not Soluble | |
|------------------|-------------------|---------------------|-----------------|
| Odour | Negligible | Melting Point | >1300°C |
| Specific Gravity | 1.2- 1.45 at 25°C | Boiling Point/Range | Not Applicable |
| рН | Not Applicable | Flash Point | Non-combustible |
| | | Page 4 of 7 | |

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES



| SAFETY DATA SHEET | BLACKWATTLE POTTERY UND | ERGLAZE COLOURS (BUG | Date of Issue: 06/02/2022 |
|----------------------|-------------------------|----------------------|---------------------------|
| Vapour Pressure | Not Applicable | Flammable Limits | Not Applicable |
| Ignition Temperature | Not Applicable | Vapour Density | Not Applicable |
| Freezing Point | Not Applicable | | |

Section 10 - STABILITY AND REACTIVITY

| Chemical Stability | Stable |
|------------------------|---------------------|
| Conditions to avoid | Avoid creating dust |
| Incompatible Materials | None known |
| Hazardous Reactions | Not Applicable |
| Polymerisation | Not Applicable |

Section 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Health Effects - Possible Routes of Exposure

| Ingestion | Ingestion of large amounts may irritate the gastric tract causing | |
|-----------------|---|--|
| | nausea and vomiting | |
| Inhalation | Inhalation of airborne dust may cause the drying and irritation of the | |
| | respiratory tract. | |
| | Acute aspiration may cause coughing, sneezing and pulmonary | |
| | edema | |
| Skin | Skin contact may cause dryness. May cause mild irritation in the case | |
| | of some individuals with sensitive skin | |
| Chronic Effects | The product contains respirable free crystalline silica in the form of | |
| | dust. Repeated exposure to respirable crystalline silica dust may lead | |
| | to silicosis, a serious lung disease. The onset of silicosis is usually | |
| | slow and lung damage may occur even when no symptoms or signs of | |
| | ill-health have occurred | |
| Eye | Eye contact may cause mechanical irritation | |
| Carcinogenicity | The product contains >20% respirable crystalline. Crystalline silica | |
| | has been classified by International Agency for Research on Cancer | |
| | (IARC) as carcinogenic to humans by inhalation (Group 1). | |
| | Furthermore, crystalline silica can cause silicosis or other lung | |
| | diseases on prolonged exposure | |

Classification of Hazardous Ingredients

Ingredient Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

Page 5 of 7

SAFETY DATA SHEET: **BLACKWATTLE POTTERY UNDERGLAZE COLOURS (BUG)** Issued by: Blackwattle Pottery Pty.Ltd. Version No. 3



12 - ECOLOGICAL INFORMATION

| Ecotoxicity | No data available |
|----------------------------|-------------------|
| Persistence/ Degradability | No data available |
| Mobility | No data available |
| Bio accumulative Potential | No data available |

Do not discharge into waterways or sewer.

13 - DISPOSAL CONSIDERATIONS

Disposal Methods The disposal of the waste or spilled material must be done in accordance with the applicable local, state and federal government regulation

Biological Limit Values No limit is allocated

Do not discharge into drains, waterways or sewer.

Recycle where possible

14 - TRANSPORT INFORMATION

Transport Information Not classified as dangerous goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail

| UN Number | None allocated |
|------------------------------|----------------|
| UN Proper Shipping Name | None allocated |
| Class and Subsidiary Risk(s) | None allocated |
| Packing Group | None allocated |

15 - REGULATORY INFORMATION

 Poisons Schedule
 Not scheduled

 Not classified as hazardous according to the criteria of the NOHSC

 Not classified as dangerous goods according to the ADG (Australian Dangerous Goods) Code

16 - OTHER INFORMATION



The SDS is a Hazard Communication Tool and should be used to assist in a Risk Assessment Program applied to the use of this material. Scale and frequency of use and controls must be considered.

Legend/Keywords

STEL Short Term Exposure Limit TWA Time Weighted Average. The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Contact phone number (02) 98295555 (bus. hours)

The information contained in this Safety Data Sheet is correct to the best of our knowledge at the date of publication and whilst every care has been exercised in the preparation, Blackwattle Pottery accepts no responsibility for any use which may be made of the contents