

SAFETY DATA SHEET BLACKWATTLE POTTERY UNDERGLAZE COLOURS (BUG)

Date of Issue: 06/02/2022

## Section 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### **Product Identifier**

Product Name: BLACKWATTLE POTTERY UNDERGLAZE COLOURS

Product Code: **BUG** 01 Witchetty White, 02 Dragonfly Yellow, 04 Grasshopper Green, 05 Thrip Green, 06 Cricket Green, 09 Cuttle Bug Purple, 10 Stinkbug Pink, 11 Butterfly Blue, 12 Beetle Blue, 13 Scarab Blue, 14 Nymph Flesh, 15

Moth Brown, 17 Slater Grey, 18 Earwig Black

Other means of identification: Not Available

#### Relevant uses of the material:

Relevant identified uses: Ceramic, Glass and Pottery

Based on available information, (provided the product is handled in accordance with this Safety Data Sheet, and used as supplied i.e. moist) is not classified as hazardous according to criteria of NOHSC.

#### **Details of the Supplier of the SDS:**

Registered Company Name: Blackwattle Pottery Pty. Ltd.

Address: 8 Aero Rd. INGLEBURN NSW 2565 Australia

Telephone: 02 9829 5555

Email: blackwattlepottery@bigpond.com Website: www.store.blackwattle.net.au

#### **Emergency telephone number**

Emergency telephone number: 02 9829 5555 Business Hours

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

### **Section 2 - HAZARDS IDENTIFICATION**

Hazard Classification Classified as non-hazardous according to the criteria of NOHSC

Poisons Schedule: Not Applicable

Risk Phrases Not hazardous, no criteria found

Safety Phrases S22 Do not breath dust

Precautionary Statement(s) Prevention: Not Applicable

Precautionary Statement(s) Response: Not Applicable

Precautionary Statement(s) Storage: Not Applicable

Precautionary Statement(s) Disposal: Not Applicable



MATERIAL	PERCENTAGE	ACGIH TLV	
Zirconium Silicate	0 - 9%	5mg / m³ (as Zr)	
Clay/ Potash	< 15%	Not Applicable	
Calcined Alumina	0 - 2%	10mg / m <sup>3</sup>	
Silica	0 - 6%	0.1mg / m <sup>3</sup>	
Zinc Oxide	0 - 10%	2mg / m <sup>3</sup>	
Lithium Carbonate	0 - 10%	Not Applicable	
Magnesium Carbonate	0 - 6%	Not Applicable	

### Section 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Proportion
Clay	1332-58-7	< 15%
Silica	14808-60-7	0-6%
Zirconium Silicate	10101-52-7	0 - 9%
Potash	1302-78-9	< 15%
Calcined Alumina	1344-28-1	0 - 2%
Zinc Oxide	1314-13-2	0 - 10%
Lithium Carbonate	554-13-2	0 - 10%
Magnesium Carbonate	7760-50-1	0 - 6%

#### **Section 4 - FIRST AID MEASURES:**

Eye Contact If this product comes in contact with the eyes: rinse thoroughly with plenty of water for at least

15 minutes and consult a physician if irritation persists.

Ingestion Rinse mouth. Do not induce vomiting. Seek medical advice.

There is a danger of cumulative effects through ingestion and/or inhalation of silica dusts with

prolonged or repeated exposures that may lead to delayed lung injury.

Inhalation Move to fresh air. If breathing has stopped, apply artificial respiration and seek medical

attention.

Skin contact Wash off with soap and water.

General Information: You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126. Have this SDS with you when you call.

Advice to any immediate medical attention and special treatment needed: Treat symptomatically



#### **Section 5 - FIRE FIGHTING MEASURES**

Suitable Extinguishing Use appropriate fire extinguishing media for surrounding combustion

materials involved in the fire

Media Specific Methods Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective

clothing to prevent exposure to vapors, fumes, dust or products of combustion

Specific Hazards The product is noncombustible

HAZCHEM Not Applicable

#### **Section 6 - ACCIDENTAL RELEASE MEASURES:**

Clean up/Disposal For small spills, pick up as much as possible, wipe area clean with damp sponge. For large spills,

pick up as much as possible, dispose of in closed containers, wash area with plenty of water.

Floors and work areas should be mopped with water.

Do not sweep work areas with a broom. Avoid the creation of airborne dust.

Environment No special environmental precautions required.

Personal Protection Wear apron or overalls, rubber gloves, chemical gloves or safety glasses.

### **Section 7 - HANDLING AND STORAGE:**

**Precaution for Safe Handling** 

Wear personal protective equipment.

Do not allow clothing wet with material to stay in contact with skin as this is likely to irritate skin.

Wash thoroughly after handling.

Keep containers sealed when not in use.

Condition for Safe Storage:

Store away from consumables.

Store in a cool place, away from heat and sunlight.

Storage incompatibility: None Known

## Section 8 - EXPOSURE STANDARDS/ PERSONAL PROTECTION

National Exposure Standards Name



STEL STEL TWA TWA

(mgm3) (ppm) (mgm3) (ppm)

Silica 0.1

Biological Limit Values No limit is allocated

Other Exposure Information No exposure standard is established for this material by the National Occupational

Health & Safety Commission (NOHSC), Australia, however the exposure standard for respirable crystalline silica, in the form of quartz, as set by NOHSC is given above. The exposure limit for dust otherwise not specified is TWA 0.1 mg/m3 (inspirable fraction)

Engineering Controls Good ventilation adequate to maintain the concentration below exposure standards is

required. The use of a local exhaust ventilation system (drawing dust away from workers breathing zone) is recommended. If the engineering controls are not sufficient to

maintain concentrations of particulates below the exposure standards, suitable

respiratory protection must be worn.

#### **Exposure Controls/ Personal Protective Equipment**

Eye/Face Protection Appropriate eye/face protection should be worn if generating dust. Final choice of

appropriate eye/face protection will vary according to individual circumstances.

Skin Protection Wear impervious protective gloves and protective clothing if skin contact is likely whilst

working with this material.

Respiratory Protection If engineering controls are not effective in controlling airborne exposure then an

approved respirator with replaceable particulate filters should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in

order to make any necessary changes for individual circumstances.



WARNING If clay dries to powder use PPE and avoid breathing dust.

#### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid Not Soluble

Odour Negligible Melting Point >1300°C

Specific Gravity 1.2- 1.45 at 25°C Boiling Point/Range Not Applicable

pH Not Applicable Flash Point Non-combustible

Page 4 of 7

SAFETY DATA SHEET: **BLACKWATTLE POTTERY UNDERGLAZE COLOURS (BUG)** Issued by: Blackwattle Pottery Pty.Ltd.

Version No. 3



Vapour Pressure Not Applicable Flammable Limits Not Applicable

Ignition Temperature Not Applicable Vapour Density Not Applicable

Freezing Point Not Applicable

#### Section 10 - STABILITY AND REACTIVITY

Chemical Stability Stable

Incompatible Materials None known

Hazardous Reactions Not Applicable

Polymerisation Not Applicable

### Section 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Health Effects - Possible Routes of Exposure

Ingestion	Ingestion of large amounts may irritate the gastric tract causing nausea and vomiting	
Inhalation	Inhalation of airborne dust may cause the drying and irritation of the respiratory tract.  Acute aspiration may cause coughing, sneezing and pulmonary	
	edema	
Skin	Skin contact may cause dryness. May cause mild irritation in the case of some individuals with sensitive skin	
Chronic Effects	The product contains respirable free crystalline silica in the form of dust. Repeated exposure to respirable crystalline silica dust may lead to silicosis, a serious lung disease. The onset of silicosis is usually slow and lung damage may occur even when no symptoms or signs of ill-health have occurred	
Eye	Eye contact may cause mechanical irritation	
Carcinogenicity	The product contains >20% respirable crystalline. Crystalline silica has been classified by International Agency for Research on Cancer (IARC) as carcinogenic to humans by inhalation (Group 1). Furthermore, crystalline silica can cause silicosis or other lung diseases on prolonged exposure	

# **Classification of Hazardous Ingredients**

**Ingredient Risk Phrases** 

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.



SAFETY DATA SHEET BLACKWATTLE POTTERY UNDERGLAZE COLOURS (BUG)

### 12 - ECOLOGICAL INFORMATION

Ecotoxicity No data available

Persistence/ Degradability No data available

Mobility No data available

Bio accumulative Potential No data available

Do not discharge into waterways or sewer.

### 13 - DISPOSAL CONSIDERATIONS

Disposal Methods The disposal of the waste or spilled material must be done in accordance with the applicable local, state and federal government regulation

Date of Issue: 06/02/2022

Biological Limit Values No limit is allocated

Do not discharge into drains, waterways or sewer.

Recycle where possible

### **14 - TRANSPORT INFORMATION**

Transport Information Not classified as dangerous goods according to the Australian Code for the Transport of

Dangerous Goods by Road and Rail

UN Number None allocated

UN Proper Shipping Name None allocated

Class and Subsidiary Risk(s) None allocated

Packing Group None allocated

#### 15 - REGULATORY INFORMATION

Poisons Schedule Not scheduled

Not classified as hazardous according to the criteria of the NOHSC

Not classified as dangerous goods according to the ADG (Australian Dangerous Goods) Code

### 16 - OTHER INFORMATION



#### SAFETY DATA SHEET

## **BLACKWATTLE POTTERY UNDERGLAZE COLOURS (BUG)**

Date of Issue: 06/02/2022

The SDS is a Hazard Communication Tool and should be used to assist in a Risk Assessment Program applied to the use of this material. Scale and frequency of use and controls must be considered.

# Legend/Keywords

STEL Short Term Exposure Limit TWA Time Weighted Average. The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

# Contact phone number (02) 98295555 (bus. hours)

The information contained in this Safety Data Sheet is correct to the best of our knowledge at the date of publication and whilst every care has been exercised in the preparation, Blackwattle Pottery accepts no responsibility for any use which may be made of the contents